

(h) VSAT operators licensed pursuant to this section are prohibited from using remote earth stations in their networks that are not designed to stop transmissions from their remote earth stations when synchronization with the target satellite fails.

[56 FR 66001, Dec. 20, 1991, as amended at 62 FR 5929, Feb. 10, 1997; 66 FR 31560, June 12, 2001; 70 FR 32254, June 2, 2005; 70 FR 33376, June 8, 2005]

**§ 25.135 Licensing provisions for earth station networks in the non-voice, non-geostationary mobile-satellite service.**

(a) Each applicant for a blanket earth station license in the non-voice, non-geostationary mobile-satellite service shall demonstrate that transceiver operations will not cause unacceptable interference to other authorized users of the spectrum, based on existing system information publicly available at the Commission at the time of filing, and will comply with operational conditions placed upon the systems with which they are to operate in accordance with § 25.142(b). This demonstration shall include a showing as to all the technical parameters, including duty cycle and power limits, under which the individual user transceivers will operate.

(b) Transceiver units associated with the non-voice, non-geostationary mobile-satellite service may not be operated on civil aircraft. All portable or hand-held transceiver units (including transceiver units installed in other devices that are themselves portable or hand-held) having a receiver operating in the 137–138 MHz band shall bear the following statement in a conspicuous location on the device: “This device may not be operated while on board a civil aircraft. It must be turned off at all times while on board such an aircraft.” This subsection shall not apply to transceiver units whose receivers are incapable of radiating in the 108–137 MHz frequency bands.

(c) Transceiver units in this service are authorized to communicate with and through U.S. authorized space stations only. No person without an FCC license for such operation may transmit to a space station in this service from anywhere in the United States ex-

cept to receive service from the holder of a pertinent FCC blanket license or from another party with the permission of such a blanket licensee.

(d) The holder of an FCC blanket license for operation of transceivers for communication via a non-voice, non-geostationary mobile-satellite system shall be responsible for operation of any such transceiver to receive service provided by the blanket licensee or provided by another party with the blanket licensee’s consent. Operators of non-voice, non-geostationary mobile-satellite systems shall not transmit communications to or from user transceivers in the United States unless such communications are authorized under a service contract with the holder of a pertinent FCC blanket license or under a service contract another party with authority for such transceiver operation delegated by such a blanket licensee.

[58 FR 68059, Dec. 23, 1993, as amended at 69 FR 5710, Feb. 6, 2004]

**§ 25.136 Licensing provisions for user transceivers in the 1.6/2.4 GHz, 1.5/1.6 GHz, and 2 GHz Mobile Satellite Services.**

In addition to the technical requirements specified in § 25.213, earth stations operating in the 1.6/2.4 GHz and 1.5/1.6 GHz Mobile Satellite Services are subject to the following operating conditions:

(a) User transceiver units associated with the 1.6/2.4 GHz Mobile-Satellite Service or 2 GHz Mobile-Satellite Service may not be operated on civil aircraft unless the earth station has a direct physical connection to the aircraft cabin or cockpit communication system.

(b) No person without an FCC license for such operation may transmit to a space station in this service from anywhere in the United States except to receive service from the holder of a pertinent FCC blanket license or from another party with the permission of such a blanket licensee.

(c) The holder of an FCC blanket license for operation of transceivers for communication via a 1.6/2.4 GHz, 1.5/1.6 GHz, or 2 GHz Mobile Satellite Service system shall be responsible for operation of any such transceiver to receive